



PrintBox 9000 : Mobile and Desktop Printing over Wi-Fi, Network, Cloud or USB for Labels, Ticketing and Receipts



Model	PrintBox 9000
Standard Ports	Ethernet, (4) USB 2.0
Keys	Not Required
SQL Database Support	Standard
Housing	Network-connected
USB 2.0 Ports	4
Printer Compatibility	ZPL or ESC/POS As Standard, others by request
Programming & Designing Templates	Web-Enabled or USB Stick Updates for standard ZPL or ESC/POS Templates. Multiple template design options available: PC Applications or custom build

PRINTBOX 9000

- Desktop and Mobile printing can be accessed from the same PrintBox by using ANY device with a web browser: PC, RFiD terminal, Smartphone or Tablet.
- A Wi-Fi or network infrastructure is not always necessary as the PrintBox can generate its own connectivity. For maximum connectivity flexibility the PrintBox also supports Bluetooth.
- Not Only is the PrintBox a multi-user Desktop & Mobile Printing standalone solution but it can also be connected to a local server to pull data to populate templates or to a cloud environment to synchronize data.
- SQL database management standard.

PrintPad 900 Series with Alphanumeric Keyboard

If an alphanumeric keypad is required with similar PrintBox 9000 functionality, see the CloudBox 900 Series.

AppiWorx & PrintWorx

Recognizing the need to create custom label formats without having to write application software, PrintWorx is an easy-to-use embedded label design application on the PrintBox 970 and PrintPad 9000. For mobile capability in a standalone environment, PrintWorx can run on the PrintBox using Wi-Fi connectivity to smart devices and mobile printers.

Electrone Ltd, Tithe House, 15 Dukes Ride, Crowthorne, Berkshire RG45 6LZ UK Phone 01344-512-029

info@electrone.biz

• www.iprintlabels.com

CloudBox Inc., 2127 10th Avenue, Vero Beach, FL 32960, Phone 646-757-1456

info@cloudboxinc.com

• www.iprintlabels.com

Specifications		9000 Linux PrintBox	Features
Design	Design	Fully enclosed Linux-based solution containing hardware and software tailored to print standard or custom labels, receipts and/or tickets via any smart device with a browser to access the print options available.	- Ethernet port connection - Uses ZPL and ESC/POS commands. Others upon request - Custom cables available to connect to a range of receipt and label printers. 4 * USB 2.0 Port. - USB Ports for printer, scanner, scale or keyboard connections - Works with a wide range of Printers – Direct or Networked - Real Time Clock feature for time and date sensitive applications
	Warranty	12 months RTB	
Physical			
Enclosure Mold		Black ABS: Terluran	
Enclosure Color		Black	
Operating Temperature		14°F ±122°F -10°C ± 50°C	
Operating Humidity		10% - 90% relative humidity	
Power Consumption		500-800mA	
Certifications		FCC, CE, RoHS	
Power		6.5—32V Input	
Dimensions			- Runs on Linux OS with Full SQL database - Includes custom Command Set for flexible printing functionality - Wi-Fi and Bluetooth connectivity - Automatic label template updates over the network or from USB stick
Length		118 mm / 4.6"	
Height		53mm / 2.1"	
Width		79 mm / 3"	

